



CONNEX500

Connex500

The First Multi-material 3-Dimensional Printing System

Bring your models closer to your end products
with innovative Objet inkjet-based Technology

- Closer-than-ever simulation of end products combining multiple materials
 - Multi-material parts: simultaneous jetting of different model materials
 - Mixed tray: different parts made with different materials in a single build
- Wide range of FullCure® and composite materials: photopolymer model and support materials; on-the-fly composite Digital Materials™
- Variety of build process and printing modes
- Boost your creativity with multiple materials and composite materials featuring varied material properties and tones
- Outstanding quality and accuracy
- 16-micron, high-resolution layers ensure smooth surfaces and fine details
- Superb productivity with large-size build tray of 500x400x200 mm
- Ease-of-use in an office environment

Technical Specifications

Layer Thickness (Z-axis)

Horizontal build layers down to 16-micron

Tray Size (XxYxZ)

500x400x200 mm (19.7x15.7x7.9 inch)

Net Build Size (XxYxZ)

490x390x200 mm (19.3x15.4x7.9 inch)

Build Resolution

X-axis: 600 dpi

Y-axis: 600 dpi

Z-axis: 1600 dpi

Printing Modes

Digital Material (DM): 30-micron (0.001 inch)

High Quality (HQ): 16-micron (0.0006 inch)

High Speed (HS): 30-micron (0.001 inch)

Typical Accuracy

20-85um for features below 50mm

Up to 200um for full model size
(for rigid materials only, depending on geometry, build parameters and model orientation)

Supported Model Materials

- FullCure®720 General Purpose, transparent material
- Vero Family opaque materials
- DurusWhite Polypropylene-like material
- Tango Family rubber-like flexible material

Digital Materials

Wide range of composite materials fabricated on the fly

Support Type

- FullCure®705 Support
- Non-toxic gel-like photopolymer support easily removed by WaterJet

Materials Cartridges:

- Four sealed 3.6 kg (7.9 lb) cartridges
- Tango family and DurusWhite also available as 1.44kg (3.17 lb) net weight in 3.6 kg casing
- Two different model materials loaded
- Front loading for quick replacement

Power Requirements

110–240 VAC 50/60 Hz

1.5 KW single phase

Machine Dimensions (WxDxH)

1420x1120x1130 mm

(55.9x44.1x44.5 inch)

Machine Weight

Net 500kg (Net 1102 lb)

Operational Environment

18°C to 22°C (64.5°F to 71.5°F)

Relative Humidity 30 – 70%

Compatibility

Windows XP, Windows Vista

Software

Objet Studio™ for Connex500 features:

- Easy selection of materials including Digital Materials
- Part separation into sub-assemblies
- Automatic real time support structure generation
- Suggested build orientation and speed, auto-place
- Slice on the fly
- Network version

Input Formats

STL, OBJDF and SLC Files

CADMatrix™ Add-in

CADMatrix add-in enables designers and engineers to seamlessly assign Objet model materials to multi-part, multi-material designs within CAD software*, thus allowing for increased control of 3D model validation.

Special Facility Requirements

None

Print Heads

8 Units

Network Communication

LAN – TCP/IP

* CAD software: CADMatrix™ is compatible with the following: Pro/ENGINEER®, SolidWorks, AutoDesk Inventor



www.stratasys.com | www.objet.com | objet-info@stratasys.com



© 2012 Stratasys Ltd. All rights reserved. Stratasys, Stratasys logo, Objet, For a 3D World, Objet24, Objet 30 Pro, Objet Studio, Quadra, QuadraTempo, FullCure, SHR, Eden, Eden250, Eden260, Eden260V, Eden 330, Eden350, Eden350V, Eden500V, Jo Manager, CADMatrix, Connex, Objet260 Connex, Connex350, Connex500, Alaris, Alaris30, PolyLog, TangoBlack, TangoGray, TangoPlus, TangoBlackPlus, VeroBlue, VeloBlack, VeroBlackPlus, VeroClear, VeroDent, VeroGray, VeroWhite, VeroWhitePlus, Durus, Digital Materials, PolyJet, PolyJet Matrix, ABS-like and ObjetGreen are trademarks or registered trademarks of Stratasys Ltd. and/or its subsidiaries or affiliates and may be registered in certain jurisdictions. All other trademarks belong to their respective owners.